www.woundwo.com



WINGLIGHT SUN SHADE WITH STYLE AND CLASS **MAXIMUM VERSATILITY** FOR OUTDOOR LIVING FOR THAT **EXTRA** BIT OF **SHADE**






Nothing is better at adapting to your personal preferences than the new WINGLIGHT double sided jointed arm awning. This is because the WINGLIGHT comes in two versions, thus giving you complete freedom in your decision-making.

The main benefits at a glance:

- Shading for large, open spaces up to 49 m²
- Awning fabrics can extend and retract either in synch or asynchronously on both sides
- Weather-proof, dirt-repelling and light-fast fabrics
- Fabric and jointed arms perfectly protected by design



WINGLIGHT COMPACT

Both awning fabrics extend and retract in synch on both sides

Single-shaft system, one motor

System width max.: 5,500 mm

Max. projection on each side: 3,500 mm

Max. shaded area: 38.5 m²

Max. system height: 3,000 mm

WINGLIGHT SOLID

Awning fabrics can also extend and retract asynchronously on both sides

Double-shaft system, two motors

System width max.: 7,0
Max. projection on each side: 3,5
Max. shaded area: 49
Max. system height: 3,2

7,000 mm 3,500 mm 49 m² 3,250 mm

Optional: LED LIGHTING

Three possible arrangements: on the inside of the upright posts, on the outside of them or at all their four corners

Option: lighting along the entire length of the support tube, other arrangements on request

SUPPORT TUBE

For system widths > 5,500 to 7,000 mm standard, opens up many more possibilities such as attaching LED lighting and heaters.

Also available for system widths up to 5,500 mm as an option.

HINGED SUPPORT



OPERATION

Get control at the touch of a button with the tried-andtested Somfy io radio motor

INSTALLATION VARIANTS

Standard version with cantilever feet, can alternatively be fixed to the substrate with either two flanged plates or two ground sleeves

Standard version with flanged plates, can alternatively be fixed to the substrate with either cantilever feet or ground sleeves

Ballast box

This installation option creates a secure and stable base for the WINGLIGHT COMPACT and WINGLIGHT SOLID, without the need for complex and expensive foundation work.

WALL BRACKET

Both WINGLIGHT versions are available with a wall bracket on one side.

UPRIGHT POST PROFILE AND ELECTRICAL INSTALLATION

The load-bearing elements of the two WINGLIGHT versions are the two solid extruded aluminium upright post profiles, (160 x 80 mm). All neat and tidy: the electrical installations and any power packs required can be stored out of sight in the cavity inside the two upright post profiles.